

Data sheet

| | |
|----------------|----------------------------|
| ID | AK |
| Description | distribution box |
| Colour | white, similar to RAL 9010 |
| Classification | AC 400 V |



Norms: ÖVE/ÖNORM EN 60670-1:2014, ÖVE/ÖNORM EN 60670-22:2007



Halogen free

False

Degree of protection (IP)

IP30

| Art. no. | Dimensions Ø/LxB x T | Small Package | Large Package |
|----------|----------------------|---------------|---------------|
| 020 921 | 200 x 400 x 70 mm | 5 pc | - |
| 020 922 | 600 x 200 x 70 mm | 6 pc | - |
| 020 923 | 400 x 400 x 70 mm | 4 pc | - |

Further technical details

| Details | |
|------------------------------|-------|
| break-out opening | True |
| seal membrane | False |
| nozzle | False |
| step membrane | False |
| Mounting switching equipment | |
| Luminaire hook mounting | False |
| Nozzle | None |
| With nail lugs | False |
| Circuit integrity | None |

| Details | |
|------------------------------|-------------------------|
| Model | Single |
| Shape | Rectangular |
| Mounting method | Flush mounted (plaster) |
| With screws | False |
| Provided with revolving ring | False |
| Connectable | False |
| Equipped with | None |
| Cover attachment | Screwed |
| Material | PVC-U |