

Data sheet

ID	J...B AP LG
Description	distribution box
Colour	light grey, similar to RAL 7035
Classification	IP65/66

Norms: EN 60670-1, EN60670-22, EN60695-2-10

halogenfree according to EN 60754



Working temperature	Degree of protection (IP)	UV-Level*
-5 to 60 °C	IP65	L3

Art. no.	Dimensions Ø/LxB x T	ps	pl
105 641	85 x 85 x 55 mm	5 pc	120 pc
105 643	100 x 100 x 60 mm	6 pc	90 pc
105 851	155 x 100 x 70 mm	1 pc	56 pc
105 852	200 x 155 x 85 mm	1 pc	20 pc

Further technical details

Details	
Halogen free	True
Tackable	False
Number of inlets	7
Type of housing feed-through	Trimable step membrane
Equipped with	None
Cover model	Mounting cover
Explosion-tested version	False
Weatherproof	True
Material	PP-Blend

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.