


Data sheet

Part No.	PKG MP GR
Description	enclosure box, jetting water tight for surface installation, suitable for damp locations, with pre-punched conduit entries
Colour	grey, similar to RAL 7037
Classification	AC 690 V, IP 65



Standard: EN 60670-22



Working temperature	Degree of protection (IP)	UV-Level*
-25 to +60 °C	IP65	L2

Art. no.	Dimensions Ø/LxW x D	For tube diameter	ps	pl
020 752	105 x 105 x 64 mm	25 mm	5 pc	50 pc
020 753	200 x 150 x 85 mm	25 mm	2 pc	12 pc

Further technical details

Details	
Halogen free	False
Tackable	False
Number of inlets	6
Type of housing feed-through	Preembossing
Equipped with	None
Cover model	Mounting cover
Explosion-tested version	False
Weatherproof	False
Material	PVC-U

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.