


Data sheet

| | |
|-------------|---|
| Part No. | SB GR |
| Description | normal bend for the connection of rigid conduits in an angle of 90°, especially für enclosed installations |
| Colour | grey, similar to RAL 7037 |



Standard: EN 61386-1, EN 61386-21



UV-Level*
L2

| Art. no. | For tube diameter | Radius | ps | pl |
|----------|-------------------|--------|-------|---------|
| 020 615 | 16 mm | 50 mm | 50 pc | 400 pc |
| 020 616 | 20 mm | 70 mm | 25 pc | 300 pc |
| 020 617 | 25 mm | 95 mm | 20 pc | 160 pc |
| 020 618 | 32 mm | 125 mm | 50 pc | 1200 pc |
| 020 619 | 40 mm | 160 mm | 35 pc | 840 pc |
| 020 620 | 50 mm | 210 mm | 20 pc | 480 pc |
| 020 621 | 63 mm | 270 mm | 8 pc | 280 pc |

Further technical details

| Details | |
|-----------------------------------|---------|
| Model | Plug-in |
| With inspection opening and cover | False |
| Angle of bow | 90 ° |
| Material | PVC-U |

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure color fastness and stability.